

08/25/00
JC916 U.S. PTO

08-28-00
IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

A
jc864 U.S. PTO
09/648822
08/25/00

PATENT APPLICATION

Jurgen Gripp
Martin Zirngibl

CASE 2-35

TITLE Optical Router

ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

SIR:

NEW APPLICATION UNDER 37 CFR § 1.53(b)

Enclosed are the following papers relating to the above-named application for patent:

Specification
8 Informal Sheets of drawing(s)
1 Assignment(s) with Cover Sheet
Declaration and Power of Attorney
Information Disclosure Statement


CLAIMS AS FILED				
	NO. FILED	NO. EXTRA	RATE	CALCULATIONS
Total Claims	27 - 20 =	7	x \$18 =	\$126
Independent Claims	6 - 3 =	3	x \$78 =	\$234
Multiple Dependent Claims, if applicable			+ \$260 =	\$0
Basic Fee				\$690
			TOTAL FEE	\$1050

Please file the application and charge **Lucent Technologies Deposit Account No. 12-2325** the amount of \$1050, to cover the filing fee. Duplicate copies of this letter are enclosed. In the event of non-payment or improper payment of a required fee, the Commissioner is authorized to charge or to credit **Deposit Account No. 12-2325** as required to correct the error.

The Assistant Commissioner for Patents is hereby authorized to treat any concurrent or future reply, requiring a petition for extension of time under 37 CFR § 1.136 for its timely submission, as incorporating a petition for extension of time for the appropriate length of time if not submitted with the reply.

Please address all correspondence to **Docket Administrator (Room 3C-512), Lucent Technologies Inc., 600 Mountain Avenue, P.O. Box 636, Murray Hill, New Jersey 07974-0636**. However, telephone calls should be made to me at 908-582-3246.

Respectfully,



Ozer M.M. Teitelbaum
Reg. No. 36698
Attorney for Applicant(s)

Date: 8/25/00
Lucent Technologies Inc.
600 Mountain Avenue (Room 3C-512)
P.O. Box 636
Murray Hill, New Jersey 07974-0636

"Express Mail" mailing label
number: EK 509325396 US
Date of Deposit: 8/25/00
I hereby certify that this Application is
being deposited with the United States Postal
Service "Express Mail Post Office to
Addressee" service under 37 CFR 1.10 on the
date indicated above and is addressed to the
Commissioner of Patents and Trademarks
Washington, D.C. 20231.
IRIS F. THOMAS
(Printed name of person mailing paper or fee)
Iris F. Thomas
(Signature of person mailing paper or fee)

OPTICAL ROUTER

CROSS-REFERENCE TO RELATED APPLICATIONS

Related subject matter is disclosed in co-pending, commonly assigned,
5 U.S. Patent application Serial Number 09/430318, filed on October 29, 1999.

FIELD OF THE INVENTION

The present invention relates to communications, generally, and more particularly to an optical router well suited for Internet Protocol ("IP") traffic.

BACKGROUND OF THE INVENTION

The rapid growth of Internet traffic has created an increasing need for more responsive inter-networking components. One component approaching its operative limits is the IP router. IP routers route packets of data traffic between
15 destinations in an inter-network.

Presently, IP routers are electronic switch based devices. To date, electronic switch based IP routers having 16 input and 16 output channels are commercially available. Extending the number of input and output channels, however, has raised substantial challenges due to the space management issues, power and heat dissipation, as well as electromagnetic interference. It is believed that given their limited number of input and output channels, electronic switch
20 based IP routers may very shortly reach their capacity to route inter-network traffic. As a result, optically based components, including IP routers, are being explored by industry. It is estimated that optical IP routers may soon be realized
25 having 128 input and 128 output channels, and thus, greater overall throughput.

In view of the above, a demand exists for an optical IP router offering an increased number of input and output channels, and greater overall throughput.

SUMMARY OF THE INVENTION

In co-pending, commonly assigned, U.S. Patent application of Brinkman et al., Serial Number 09/430,318, filed on October 29, 1999, an optical router is described for routing signals by determining an intended destination for a packet

to be routed, appropriately “coloring” the packet according to a selected wavelength in a destination-specific manner, and then transmitting the colored packet through an optical frequency router. By this arrangement, the colored packet of data is routed to a desired destination.

5 We have invented an optical router having increased throughput over the hereinabove referenced U.S. patent application. Our optical router employs an optical frequency router for simultaneously receiving at least two signals which are differently “colored” – having different wavelengths - in one input port. The optical frequency router also simultaneously presents at least two routed signals
10 which are differently “colored” – having different wavelengths - at one output port. By this arrangement, a number of colored packets of data may be simultaneously routed to each of their desired destinations through one port.

15 In an illustrative embodiment of the present invention, an optical router is disclosed. The optical router comprises a plurality of combiners, a plurality of receivers, and at least one optical frequency router for routing optical signals by their color. To increase the number of input and output channels of the optical router, at least one input port of the frequency router is coupled with one combiner for combining optical signals of different colors, while at least one output port of the optical frequency router is coupled with one receiver for
20 separating and directing at least two frequency routed optical signals to their intended destinations.

These and other embodiments, advantages and objects will become apparent to skilled artisans from the following detailed description read in conjunction with the appended claims and the drawings attached hereto.

25 **BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention will be better understood from reading the following description of non-limiting embodiments, with reference to the attached drawings, wherein below:

FIG. 1 illustrates a first embodiment of the present invention;

30 **FIG. 2** illustrates a second embodiment of the present invention;

FIG. 3 illustrates a third embodiment of the present invention;

FIG. 4 illustrates a fourth embodiment of the present invention;
FIG. 5 illustrates a fifth embodiment of the present invention;
FIG. 6 illustrates a sixth embodiment of the present invention;
FIG. 7 illustrates a converter according to an embodiment of the present
5 invention; and

FIG. 8 illustrates an optical frequency router device according to an embodiment of the present invention.

It should be emphasized that the drawings of the instant application are not to scale but are merely schematic representations, and thus are not intended
10 to portray the specific parameters or the structural details of the invention, which can be determined by one skilled in the art by examination of the information herein.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

Referring to FIG. 1, an optical router 10 is illustrated according to a first
15 embodiment of the present invention. Optical router 10 routes signals from a plurality of router input channels, 12, 14, 16 and 18, to a plurality of router output channels, 38, 40, 42 and 44. Router input channels, 12, 14, 16 and 18 each receive a signal to be routed. In an embodiment of the present invention, each signal to be routed is a packet of data employing an Internet Protocol ("IP")
20 format, for example - other formats and standards, however, may also be used. Each IP packet of data has its intended destination residing therein, as will be better understood from the disclosure hereinbelow in association with FIG. 7.

Optical router 10 comprises an optical frequency router 20. Optical frequency router 20 routes optical signals in response to their wavelength or
25 color, as will be better understood from the disclosure hereinbelow in association with FIG. 8. Frequency router 20 has a plurality of input ports, 22 and 24, and a plurality of output ports, 26 and 28.

Optical router 10 also comprises a pair of input devices, 30 and 32. Input devices, 30 and 32, convert received packets of data into corresponding optical
30 signals. Each optical signal, as converted, is "colored" in response to the intended destination information of the respective packet of data. The resultant optical

signal, as colored, has a wavelength corresponding with an intended output port, **26** or **28**, to which it is to be routed to by frequency router **20**.

Each input port, **22** and **24**, of frequency router **20** is respectively coupled with an input device, **30** and **32**. Likewise, each input device, **30** and **32**, is coupled with a group of router input channels, **12** and **14**, and, **16** and **18**, respectively. Each input device, **30** and **32**, may simultaneously receive more than one incoming packet of data from its respective router input channels. Consequently, each input device, **30** and **32**, may combine more than one optical signal if they are of different wavelengths or colors.

Optical router **10** comprises a centralized scheduler (not shown) for scheduling the conversion of each received packet of data into an optical signal. The scheduler enables the coloring of each optical signal in response to the intended destination information of the corresponding packet of data, to avert overlap of optical signals having the same color, also referred to as collisions. In scheduling the conversion of packets of data, the scheduler may delay one packet of data relative to another if both are to be routed to the identical router output channel. Likewise, the scheduler may delay one packet relative to another if both are received by the same input device and are to be routed through the same output port of frequency router **20** to different destinations.

In the illustrative embodiment, a number of packets of data, **1_a** and **2_a**, are simultaneously received by input device **30**, while a packet of data **2_b** is received by input device **32**. Each respective input device, **30** and **32**, converts these packets of data into corresponding optical signals, λ_{1a} , λ_{2a} and λ_{2b} - each of which are colored in response to their destination. Input device **30**, receiving packets of data, **1_a** and **2_a**, combines the converted optical signals, λ_{1a} and λ_{2a} , into a combined optical signal having two component signals. As a result, input port **22** simultaneously receives the combined optical signal. Likewise, input port **24** receives the converted optical signal λ_{2b} . Given its physical properties, frequency router **20** routes optical signals λ_{1a} and λ_{2a} from input port **22** to outputs ports **26** and **28**, respectively, and optical signal λ_{2b} from input port **24** to output port **26**.

Coupled with each output port, **26** and **28**, is a receiver, **34** and **36**. Each receiver, **34** and **36**, is also coupled with a group of router output channels, **38** and **40**, and, **42** and **44**, respectively. Each receiver, **34** and **36**, is capable of separating routed optical signal components combined by frequency router **20** at its respective output port. Each receiver, **34** and **36**, also presents - or, in other words, directs - each routed optical signal component to its respective intended destination. In the illustrative embodiment, receiver **34** simultaneously receives optical signals, λ_{1a} and λ_{2b} , from output port **26**, while receiver **36** receives optical signal λ_{2a} from output port **28**. Consequently, receiver **34** presents optical signals, λ_{1a} and λ_{2b} , to router output channels **38** and **40**, respectively, and receiver **36** presents optical signals, λ_{2a} , to router output channel **42**. Moreover, each receiver, **34** and **36**, also converts each received optical signal, λ_{1a} , λ_{2a} and λ_{2b} , back into packets of data, **1a**, **2a**, and **2b**, in the electrical domain.

Frequency router **20** comprises N input ports and N output ports, where N is equal to two (2) in the illustrative embodiment. Each input port of frequency router **20** is also capable of simultaneously receiving, N , or two (2) optical signals from a respective input device, while each output port is capable of simultaneously presenting, N , or two (2), optical signals to a respective receiver. Consequently, optical router **10** has $N \times N$ router input channels and $N \times N$ router output channels.

Referring to **FIG. 2**, an optical router **50** is illustrated according to a second embodiment of the present invention. While employing the same operational principles as optical router **10** of **FIG. 1**, the architecture of optical router **50** supports greater than $N \times N$ router input channels and $N \times N$ router output channels. Optical router **50** comprises an optical frequency router **80** having N input ports, **68**, **70** and **72**, and N output ports, **74**, **76** and **78**, where N is equal to three (3).

In the illustrative embodiment, input port **68** is capable of simultaneously receiving M , or five (5), optical signals from an input device **62** through router input channels **52**, **54**, **56**, **58** and **60**. Likewise, output port **74** is capable of simultaneously presenting M , or five (5), optical signals to a receiver **82**, and,

thus, router output channels **88, 90, 92, 94** and **96**. If the number of optical signals received by an input port exceeds the number of output ports, frequency router **80** routes two or more of these optical signals to the same output port. A data collision, however, may be avoided if these routed signals have different colors (wavelengths) and the ratio of their wavelengths satisfies the modal properties of frequency router **80**, as will be better understood from the disclosure hereinbelow in association with **FIG. 8**.

It should be apparent to skilled artisans from the hereinabove disclosure that input ports **70** and **72** may each also simultaneously receive M optical signals through input devices, **64** and **66**, respectively, while output ports **76** and **78** may each also simultaneously present to their respective receivers, **84** and **86**, M optical signals. Here, optical router **50** will have $N \times M$ router input channels and $N \times M$ router output channels. To effectively increase the number of input and output channels of optical router **50** with respect to optical router **10** of **FIG. 1**, M should be greater than N . The maximum number of input and output channels available to optical router **50** is primarily limited by the material properties of frequency router **80**.

Referring to **FIG. 3**, an optical IP router **100** is illustrated according to a third embodiment of the present invention. Optical IP router **100** routes signals from a number of router input channels, **102₁-102_M**, **104₁-104_M**, and **106₁-106_M**, to a number of router output channels, **164₁-164_M**, **166₁-166_M**, and **168₁-168_M**. Router input channels, **102₁-102_M**, **104₁-104_M**, and **106₁-106_M**, each may receive an IP packet of data having its intended destination residing therein.

Optical router **100** comprises an optical frequency router **120** for routing optical signals in response to their wavelength or color. Optical router **100** also comprises a plurality of input devices, **110₁-110_N**. Each input device converts a number of received IP packets of data from a corresponding number of router input channels into a number of colored optical signals. Each optical signal, as converted, may be "colored" in response to the intended destination information of the respective packet of data.

To effectively convert each received IP packet of data, each input device comprises a number of converters, **112₁-112_M**, **114₁-114_M** and **116₁-116_M**, each

corresponding with a router input channel, **102₁-102_M**, **104₁-104_M**, and **106₁-106_M**. Each converter comprises a tunable laser ("TL") for generating a carrier monochromatic light beam having a particular wavelength or color selected in response to a received packet of data and controlled by a centralized scheduler

5 **135**, as will be better understood from the disclosure hereinbelow in association with **FIG. 7**. The carrier light beam is subsequently modulated by a modulator in response the received packet of data, resulting in an optical data signal having a color corresponding with the intended destination of received packet of data.

Each input device, **110₁-110_N**, also comprises an optical power combiner,

10 **118₁-118_N**. Each combiner, **118₁-118_N**, is coupled with a number of corresponding converters, **112₁-112_M**, **114₁-114_M** and **116₁-116_M**, associated with a respective input device; **110₁-110_N**. Each combiner combines simultaneously received optical signals, as colored. Consequently, a plurality of combined optical signals, **125₁-125_N**, are output from each corresponding input device. It should

15 be noted that scheduler **135** prevents each combiner from combining more than one optical signal of the same color.

Frequency router **120** comprises a plurality of input ports, **130₁-130_N**, and a plurality of output ports, **140₁-140_N**. Coupled with an input device, each input port may receive a combined optical signal. Frequency router **120** routes

20 each component optical signal within a combined optical signal to an output port in response to the color of the respective signal. Thus, for example, if combined optical signal, **125₁**, comprising component optical signals from converted packets of data of each router input channel, **102₁-102_M**, is received by input port **130₁**, frequency router **120** routes each component optical signal to one

25 output port. If input ports **130₂-130_N** also receive combined optical signals, a number of routed optical signals may also be simultaneously presented to a number of output ports. Given the characteristics of frequency router **120**, the routed optical signals presented at an exemplary output port, **140₁**, will have different colors. Therefore, each output port may present a resultant optical

30 signal, **145₁-145_N**, comprising a number of component routed optical signals therein.

IP router **100** also comprises a plurality of output receivers, **150₁-150_N**. Each receiver is coupled with an output port of frequency router **120** for receiving a resultant optical signal, **145₁-145_N**. Each receiver, **150₁-150_N**, comprises an optical power splitter, **152₁-152_N**. Each splitter, **152₁-152_N**, is
5 coupled with a number of corresponding tunable filters ("TF"), **154₁-154_M**, **156₁-156_M** and **160₁-160_M**, associated with a respective receiver, **150₁-150_N**. Each splitter splits or divides the optical power of a corresponding resultant optical signal, **145₁-145_N**, amongst its respective tunable filters.

By this arrangement, each tunable filter may receive a power divided
10 representation of a resultant optical signal, **145₁-145_N**. At least one tunable filter of the corresponding receiver is tuned to the color of a component optical signal of the resultant optical signal, through scheduler **135**, in response to the intended destination of an original packet of data. The tuning of the tunable filter enables each component optical signal within a resultant optical signal to pass to its
15 intended destination.

It should be noted that optical IP router **100** prevents the simultaneously routing of more than one IP packet of data received by one input device, **110₁-110_N**, to one output receiver, **150₁-150_N**. This limitation is based on the fact that both IP packets of data would require the same coloring to be routed to the same
20 output receiver. To avert a data collision, in one embodiment, scheduler **135** introduces a delay between such IP packets of data. However, this potential limitation also enables optical IP router **100** to route one packet of data from one router input channel associated with one input device to any number of router output channels associated with one output receiver by setting some or all of the
25 corresponding tunable filters to the same color. This routing feature, also referred to as partial multicasting, allows optical IP router **100** to route, for example, one packet of data from router input channel **102₂** to router output channels **166₁-166_M**.

Referring to **FIG. 4**, an optical IP router **200** is illustrated according to a
30 fourth embodiment of the present invention. Optical router **200** operates similarly to optical IP router **100** of **FIG. 3**. However, optical router **200**

employs a two stage routing architecture to replace tunable filters, **154₁-154_M**, **156₁-156_M** and **160₁-160_M**.

The two stage architecture of optical router **200** comprises a first and a second stage optical frequency router, **220** and **260**, for routing packets of data from a number of router input channels, **202₁-202_M**, **204₁-204_M**, and **206₁-206_M**, to a number of router output channels, **280₁-280_M**, **282₁-282_M**, and **284₁-284_M**. Optical router **200** comprises a plurality of first stage input devices, **210₁-210_N**. Each input device, **210₁-210_N**, much like the input devices, **110₁-110_N**, of **FIG. 3**, comprises a number of converters, **212₁-212_M**, **214₁-214_M**, and **216₁-216_M**. Each converter comprises a tunable laser ("TL") for converting a received IP packet of data into an optical signal colored in response to its intended destination. Each input device also comprises a combiner, **218₁-218_N**, for combining the colored optical signals into a combined optical signal of a number of colors, and a scheduler **235** for preventing more than one optical signal of the same color from being combined. A combined optical signal, **222₁-222_N**, may be generated by each corresponding input device.

First stage frequency router **220** comprises a plurality of input ports, **225₁-225_N**, and a plurality of output ports, **230₁-230_N**. Each input port is associated with one input device to receive one combined optical signal, **222₁-222_N**. First stage frequency router **220** routes each optical signal component within a combined optical signal to an output port in response to its color. As such, each output port may have a resultant optical signal, **238₁-238_N**, comprising a number of simultaneously presented routed optical signals each having a different color.

Optical router **200** also comprises a plurality of second stage input devices, **240₁-240_N**, each for coupling an output port of first stage frequency router **220** with an input port, **255₁-255_N**, of second stage frequency router **260**. Each second stage input device, **240₁-240_N**, comprises a second stage demultiplexer, **242₁-242_N**, for demultiplexing a resultant optical signal, **238₁-238_N**, into a number of component, once routed, optical signals. Each second stage input device also comprises a number of second stage converters, **244₁-244_M**, **246₁-246_M**, and **248₁-248_M**, and a second stage combiner, **250₁-250_N**,

resulting in combined second stage optical signals, **252₁-252_N**. By this arrangement, each once routed optical signal component is directed to a specific second stage converter in response to its color. Each second stage converter, in response to the intended destination of the original packet of data, re-colors the received once routed optical signal component, to form a second stage optical signal.

It should be noted that each second stage converter converts a received demultiplexed routed optical signal into an electrical signal. Each second stage converter recreates the once routed optical signal component as a second stage optical signal from the electrical representation created. In response to the intended destination of the original received packet of data, the second stage optical signal is colored, as controlled by scheduler **235**.

Scheduler **235** may be realized using a centralized design. Alternatively, scheduler **235** may comprise a number of independent schedulers. Here, each input device, **210₁-210_N**, and each second stage input device, **240₁-240_N**, has an associated independent scheduler. Each independent scheduler controls the routing of packets of data corresponding with its associated input device. As a consequence, each independent scheduler need not interact with any other independent scheduler, thereby simplifying the scheduling computations associated with a centralized scheme.

Each input port, **255₁-255_N**, may receive one combined second stage optical signal, **252₁-252_N**. Second stage frequency router **260** routes each component of the combined second stage optical signals, **252₁-252_N**, as received by an associated input port, according to their color. As such, each second stage routed optical signal, **268₁-268_N**, comprises routed components of different second stage optical signals, **252₁-252_N**. The resultant routed optical signals, **268₁-268_N**, are presented by each output port, **265₁-265_N**, to a corresponding output stage receiver, **270₁-270_N**.

Each output stage receiver, **270₁-270_N**, comprises an output stage demultiplexer, **272₁-272_N**, for demultiplexing one resultant routed optical signal, **268₁-268_N**. Each resultant routed optical signal, **268₁-268_N**, may have a number of component optical signals therein. As such, each component of the

resultant routed optical signals is directed to a particular router output channel, **280₁-280_M**, **282₁-282_M**, and **284₁-284_M**, and thus, presented to the intended destination of the original packet of data.

Referring to **FIG. 5**, an optical IP router **300** is illustrated according to a fifth embodiment of the present invention. Optical router **300** operates similarly to optical IP router **200** of **FIG. 4**. However, optical router **300** enables one packet of data received by any one router input channel to be to be simultaneously routed to any number of router output broadcasting channels. This feature is defined as full multicasting or router broadcasting.

To realize this full multicasting feature, optical router **300** comprises a first and a second stage optical frequency router, **320** and **370**, for routing packets of data, between a number of router input channels, **302₁-302_N**, **304₁-304_N**, and **306₁-306_N**, and a number of router output channels, **396₁-396_M**, **398₁-398_M**, and **400₁-400_M**. Optical router **300** comprises a plurality of first stage input devices, **310₁-310_N**. Each input device, **310₁-310_N**, comprises a number of fixed lasers ("FL"), **312₁-312_M**, **314₁-314_M**, and **316₁-316_M**, for converting a received IP packet of data into an optical signal.

Unlike the previous embodiments, each optical signal may be colored in response to which fixed laser, and thus which router input channel, receives the IP packet of data. For example, each packet of data received by router input channel, **302₂**, and fixed laser **312₁**, should be similarly colored. Each input device, **310₁-310_N**, also comprises a multiplexer, **318₁-318_N**, for multiplexing, or in other words, combining each of the optical signals received from the corresponding fixed lasers, and for generating a multiplexed or combined optical signal, **322₁-322_N**.

First stage frequency router, **320**, comprises a plurality of input ports, **325₁-325_N**, each for receiving a multiplexed optical signal, **322₁-322_N**, from an input device. Frequency router, **320**, routes each component optical signal of the received multiplexed signals, **322₁-322_N**, according to its color. Frequency router, **320**, at each output port, **325₁-325_N**, presents a resultant routed optical signal, **338₁-338_N**, each of which may comprise routed components of other multiplexed signals, **322₁-322_N**.

Each output port, **330₁-330_N**, is coupled with a second stage receiver, **340₁-340_N**. Each second stage receiver comprises an optical power splitter, **342₁-342_N**, for splitting one received resultant routed optical signal from the corresponding output port amongst a number of tunable filters ("TF"), **344₁-344_M**, **348₁-348_M**, and **352₁-352_M**. Each tunable filter receives a power divided representation of a resultant routed optical signal, **338₁-338_N**, and may be tuned to the color of a component optical signal in response to the intended destination of an original packet of data by a centralized scheduler **335**. Each tunable filter may pass a component optical signal from resultant routed optical signal, **338₁-338_N**, to a corresponding fixed laser, **346₁-346_M**, **350₁-350_M**, **354₁-354_M**. Each fixed laser converts or re-colors a component optical signal, as passed by a corresponding tuned filter. Here, the resultant optical signal may be colored according to which fixed laser receives the component optical signal. For example, each component optical signal passed by tunable filter **344₂** to fixed laser **346₂** will be colored identically.

Each output device, **340₁-340_N**, also comprises a multiplexer, **356₁-356_N**, for multiplexing each of the optical signals received from the corresponding second stage fixed lasers, and for generating a second stage multiplexed optical signal, **358₁-358_N**. Further, each second stage multiplexed optical signal is received by one input port, **365₁-365_N**, of second stage frequency router, **370**. Frequency router, **370**, routes each component optical signal of the received second stage multiplexed signals, **358₁-358_N**, according to its color. Frequency router, **370**, at each output port, **375₁-375_N**, presents a final stage optical signal, **378₁-378_N**. Each final stage optical signal may comprise routed components from other second stage multiplexed signals, **358₁-358_N**.

Each output port, **375₁-375_N**, is coupled with an output stage receiver, **380₁-380_N**. Each output stage receiver comprises a power splitter, **382₁-382_N**, for splitting a final stage optical signal, **378₁-378_N**, as received from the corresponding output port, amongst a number of associated output stage tunable filters, **384₁-384_M**, **388₁-388_M**, and **392₁-392_M**. Each tunable filter receives a power divided representation of a final stage optical signal, **378₁-378_N**. One or more tunable filters may be tuned to the color of a component optical signal,

though a scheduler **335**, in response to the intended destination of an original packet of data. Consequently, the passed optical signal may be effectively routed to its intended destination via router output channels, **396₁-396_M**, **398₁-398_M**, and **400₁-400_M**.

5 Referring to **FIG. 6**, an optical IP router **450** is illustrated according to a sixth embodiment of the present invention. Optical IP router **450** is an alternative configuration of optical IP router **200** of **FIG. 4**, employing one optical frequency router **480**. It should be noted that optical IP router **300** of **FIG. 5** may also be modified in accordance with the configuration of optical IP
10 router **450**.

Frequency router **480** comprises a number of ports, **475₁-475_N** and **485₁-485_N**, each of which function in a dual role: (1) for receiving combined optical signals from a number of tunable lasers; and (2) for presenting a routed optical signal comprising a number of differently colored optical signals. Moreover,
15 frequency router **480** employs a number of circulators, **465₁-465_N** and **470₁-470_N**, each of which coupled with one port. Known to skilled artisans, optical circulators functionally separate optical signals propagating in different directions. Each circulator enables a combined optical signal and a routed optical signal having various component signals to propagate through the same port,
20 unobstructed.

For example, a packet of data is received by a converter, **455₁**, to produce an optical signal, **458₁**, colored in response to its destination. Optical signal, **458₁**, is received by combiner **460₂**, where it may be combined with other optical signals, resulting in a combined optical signal **462₂**. Circulator **465₂** allows
25 combined optical signal **462₂** to propagate to port **475₂**, while a routed optical signal, **468₂**, is presented to circulator **465₂** from port **475₂**. Routed optical signal, **468₂**, is directed by circulator **465₂** to a demultiplexer, **490₂**, for example, and directed to a number of light detecting devices, including device **495₂**.

30 Referring to **FIG. 7**, a converter **500** is illustrated as may employed in the present invention. Converter **500** receives packets of data, each of which may employ an Internet Protocol ("IP") format. Each IP packet of data comprises a

header containing source and destination identifiers, as well as a data portion. The source identifier identifies the source or origin of the packet of data, while the destination identifies the intended destination of the specific packet. The data portion of the packet contains the data to be conveyed from the source to the destination. Using converter **500**, each packet of data may be “colored” according to its destination. More specifically, an appropriate wavelength or color of light is selected for each packet of data to enable its transport through an optical frequency router to a desired output port.

Converter **500** comprises a tunable transmitter **515** and a modulator **520**. Tunable transmitter **515** may be realized by various components including a tunable laser. Upon determining the destination of each packet of data and selecting an appropriate color, tunable transmitter **515** is tuned to the appropriate color and the packet of data may be modulated by modulator **520** into an optical packet signal of the designated appropriate color. The resultant colored optical packet of data is thereafter output to a combiner, as detailed hereinabove.

The selection of an appropriate color for each packet of data in view of its destination is controlled by central scheduler **525**. Central scheduler **525** protects against data collisions if two packets of data within two converters of an input device, **110₁** of **FIG. 3**, for example, have the same destination. In such circumstances, one packet of data may be delayed by a memory device, such as a buffer **510**, before being colored.

In another embodiment of the present invention, converter **500** comprises a light detector **505**, such as a photodiode, for converting an optical packet of data into an electrical representation. The resultant electrical signal may be fed into a buffer **510** for temporary storage. Buffer **510** relays the electrical signal to modulator **520**, in response to scheduler **525**, to enable the carrier light beam from laser **515** to be modulated.

Referring to **FIG. 8**, an optical frequency router **600** is illustrated as employed in the present invention. Optical frequency router **600** is a class of electro-optical components proposed for routing optical signals. Various realizations are available presently, including a Waveguide Grating Router

005280 " 22887950

("WGR"), as is disclosed in United States Patent Numbers 5,002,350 and 5,136,671, and hereby incorporated by reference.

Frequency router **600** comprises an interconnecting apparatus having a plurality of input ports, **605₁-605_N**, each of which are connected to a free space region **610**. Frequency router **600** further comprises a plurality of output waveguides **620** extending from free space region **610**. Each output waveguides **620** of the plurality is coupled with an optical grating **630**. Optical grating **630** comprises a plurality of unequal length waveguides. The differing lengths of these waveguides cause distinct relative phase delays between optical signals propagating through optical grating **630**. Each waveguide of the plurality of unequal length waveguides is coupled with an input waveguide of a plurality of input waveguide **640**. Each input waveguide is connected to a second free space region **650**. Extending from second free space region **650** is a plurality of output ports, **655₁-655_N**. Typically, input and output ports, **605₁-605_N** and **655₁-655_N**, are respectively formed from waveguides.

It should be apparent to skilled artisans that frequency router **600** may operate as a multiplexer and/or a demultiplexer of optical frequencies. Thus, if an optical signal having an amplitude A is received by input port **605₁**, a number of optical signals are produced at the output ports **655₁-655_N**. The optical signals at the output ports **655₁-655_N** have corresponding amplitudes of AT_1 , AT_2 , AT_N , where T_i is the value of the transmission coefficient for input port **605₁** and each output port **655₁-655_N**. Furthermore, from these properties, frequency router **600** may direct an optical signal received by an input port, **605₁-605_N**, into an output port, **655₁-655_N**, in response to its wavelength or color.

While the particular invention has been described with reference to illustrative embodiments, this description is not meant to be construed in a limiting sense. It is understood that although the present invention has been described, various modifications of the illustrative embodiments, as well as additional embodiments of the invention, will be apparent to skilled artisans upon reference to this description without departing from the spirit of the invention, as recited in the claims appended hereto. It is therefore contemplated

that the appended claims will cover any such modifications or embodiments as fall within the true scope of the invention.

CLAIMS

1 **1.** An optical router comprising at least one frequency router having a
2 plurality of input ports and a plurality of output ports, at least one input port
3 simultaneously receives at least two optical signals to be frequency routed, and at
4 least one output port simultaneously presenting at least two frequency routed
5 optical signals, wherein each optical signal to be frequency routed is colored in
6 response to destination information.

1 **2.** The optical router of Claim **1**, further comprising:

2 a plurality of combiners, one combiner for combining the at least two
3 optical signals to be routed; and

4 a plurality of receivers, one receiver for separating each of the at least two
5 routed optical signals to intended destinations in response to destination
6 information.

1 **3.** The optical router of Claim **2**, wherein the frequency router routes optical
2 signals by color, the at least two optical signals to be routed having different
3 colors, and the at least two routed optical signals having different colors.

1 **4.** The optical router of Claim **3**, wherein the optical router receives packets
2 of data, each packet of data having destination information, each combiner
3 coupled with at least one converter of a plurality, each converter converting at
4 least one packet of data to an optical signal colored in response to the destination
5 information of the corresponding at least one packet of data.

1 **5.** The optical converter of Claim **4**, wherein the frequency router comprises:

2 at least one input waveguide;

3 at least one output waveguide;

4 a first and a second free space region, the first free space region coupled
5 with the at least one input waveguide and the second free space region
6 coupled with the at least one output waveguide; and

7 an optical grating having a plurality of unequal length waveguides, each
8 unequal length waveguide coupled between the first free space region and
9 the second free space region.

1 **6.** The optical router of Claim **5**, wherein each receiver comprises:

2 at least two tunable filters; and

3 at least one splitter for splitting the at least two routed optical signals
4 between the at least two tunable filters such that at least one of the at least
5 two tunable filters is tuned to pass one of the at least two routed optical
6 signals to an intended destination.

1 7. The optical router of Claim 5, wherein each receiver comprises:
2 at least two second stage converters;
3 at least one demultiplexer for separating each of the at least two routed
4 optical signals into one of the at least two second stage converters, each
5 second stage converter converting one of the routed optical signals to a
6 second stage optical signal colored in response to the destination
7 information of the corresponding at least one packet of data; and
8 at least one second stage combiner for combining second stage optical
9 signals into a combined second stage optical signal to be frequency routed.

1 8. The optical router of Claim 7, further comprising:
2 a second stage frequency router having a plurality of second stage input
3 ports and a plurality of second stage output ports, one second stage input
4 port receiving the combined second stage optical signal to be frequency
5 routed; and
6 a plurality of output stage demultiplexers, each output stage demultiplexer
7 being coupled one second stage output port of the second stage frequency
8 router such that each second stage optical signal of the combined routed
9 second stage optical signal is presented to an intended destination.

1 **9.** An optical router for routing a plurality of packets, N, of data, each packet
2 of data having destination information, the optical router comprising:

3 a plurality of converters, each converter receiving a packet of data and
4 providing an optical signal to be routed, each optical signal being colored
5 in response to the destination information of the respective packet of data;

6 a plurality of combiners, one combiner combining at least two optical
7 signals to be routed;

8 at least one frequency router having a plurality of input ports, M, and a
9 plurality of output ports, M, at least one output port simultaneously
10 receiving the at least two optical signals to be routed, and at least one
11 output port simultaneously presenting at least two routed optical signals,
12 the at least one frequency router routing optical signals by color;

13 a plurality of receivers; and

14 a plurality of splitters, one splitter splitting the at least two routed optical
15 signals between at least two receivers such that at least one of the at least
16 two receivers is tuned to pass one of the at least two routed optical signals
17 to an intended destination.

1 **10.** The optical router of Claim **9**, wherein each converter comprise a tunable
2 light source for generating one optical signal, and for coloring the one optical
3 signal in response to the destination information of the respective packet of data,
4 and wherein each receiver comprises a tunable filter for tuning to a color to pass
5 one of the at least two routed optical signals to an intended destination.

1 **11.** The optical router of Claim **10**, wherein each converter comprises a
2 converter for converting at least one packet of data to the one optical signal
3 colored in response to destination information, and wherein each receiver
4 comprises a converter for converting a routed optical signal into a routed packet
5 of data.

1 **12.** The optical router of Claim **11**, further comprising a scheduler for
2 scheduling the conversion each packet of data into an optical signal and for
3 scheduling the tuning of the tunable filter.

1 **13.** The optical converter of Claim **11**, wherein the frequency router comprises:
2 at least one input waveguide;
3 at least one output waveguide;
4 a first and a second free space region, the first free space region coupled
5 with the at least one input waveguide and the second free space region
6 coupled with the at least one output waveguide; and
7 an optical grating having a plurality of unequal length waveguides, each
8 unequal length waveguide coupled between the first free space region and
9 the second free space region.

1 14. An optical router for routing a plurality of packets, N, of data, each packet
2 of data having destination information, the optical router comprising:

3 a plurality of first stage converters, each converter receiving a packet of
4 data and providing an optical signal to be routed, each optical signal being
5 colored in response to the destination information of the respective packet
6 of data;

7 a plurality of first stage combiners, one combiner combining at least two
8 optical signals to be routed;

9 a first stage frequency router having a plurality of input ports, M, and a
10 plurality of output ports, M, at least one output port simultaneously
11 receiving the combined at least two optical signals to be routed, and at
12 least one output port simultaneously presenting at least two first stage
13 routed optical signals, the first stage frequency router routing optical
14 signals by color;

15 a plurality of second stage converters, each second stage converter
16 providing a second stage optical signal to be routed, each second stage
17 optical signal being colored in response to the destination information of
18 the respective packet of data;

19 a plurality of second stage demultiplexers, one second stage demultiplexer
20 presenting each of the at least two routed optical signals from the first
21 stage frequency router to a second stage converter;

22 a plurality of second stage combiners, one second stage combiner
23 combining at least two second stage optical signals to be routed; and

24 a second stage frequency router having a plurality of second stage input
25 ports, M, and a plurality of second stage output ports, M, at least one
26 second stage input port simultaneously receiving at least two second stage
27 optical signals to be routed, and at least one second stage output port
28 simultaneously presenting at least two second stage routed optical signals,
29 the second stage frequency router routing second stage optical signals by
30 color.

1 **15.** The optical router of Claim **14**, further comprising a plurality of output
2 stage receivers, each output stage receiver having an output stage demultiplexer,
3 one output stage demultiplexer presenting each of the at least two second stage
4 routed optical signals from the second stage frequency router to an intended
5 destination.

1 **16.** The optical router of Claim **14**, further comprising a plurality of output
2 stage receivers, each output stage receiver comprising:

3 at least two tunable filters for tuning to a color; and

4 a splitter coupled with the at least two tunable filters, wherein one output
5 stage receiver splits the at least two second stage routed optical signals
6 between the corresponding at least two tunable filters such that at least
7 one of the at least two tunable filters is tuned to pass one of the at least two
8 second stage routed optical signals to an intended destination.

1 **17.** The optical router of Claim **14**, wherein each first stage converter
2 comprises a first stage tunable light source for generating one optical signal, and
3 for coloring the one optical signal in response to the destination information of
4 the respective packet of data, each second stage converter comprises a second
5 stage tunable light source for generating one second stage optical signal, and for
6 coloring the one second stage optical signal in response to the destination
7 information of the respective packet of data, and further comprising a scheduler
8 for scheduling the coloring of each optical signal and each second stage optical
9 signal.

1 **18.** The optical router of Claim **17**, wherein each first stage converter
2 comprises a first stage converter for converting at least one packet of data to the
3 one optical signal colored in response to destination information of the respective
4 packet of data, each second stage converter comprises a second stage converter
5 for coloring one second stage optical signal in response to destination
6 information of the respective packet of data.

1 **19.** The optical router of Claim **14**, wherein at least one of the first and the
2 second stage frequency routers comprise:

3 at least one input waveguide;

4 at least one output waveguide;

5 a first and a second free space region, the first free space region coupled
6 with the at least one input waveguide and the second free space region
7 coupled with the at least one output waveguide; and

8 an optical grating having a plurality of unequal length waveguides, each
9 unequal length waveguide coupled between the first free space region and
10 the second free space region.

1 **20.** The optical router of Claim 14, wherein the first and the second
2 stage frequency routers are formed by one frequency.

1 **21.** A method for routing optical signals comprising:

2 determining a first, second and third destination for a first, second and
3 third packet of data, respectively;

4 generating a first, second and third carrier signal having a first, second
5 and third frequency associated with the first, second and third
6 destinations, respectively;

7 modulating the first, second and third carrier signals in response to the
8 first, second and third packets of data to form a first, second and third
9 optical signal; and

10 routing the first, second and third optical signals by a frequency routing
11 device, the routing comprising:

12 simultaneously receiving in a first input of a frequency router at
13 least two of the first, second and third signals; and

14 simultaneously presenting from a first output of the frequency
15 router at least two of the first, second and third routed optical
16 signals.

1 **22.** A method for routing a plurality of optical signals as a function of color
2 through a router having a plurality of inputs and a plurality of outputs, the
3 method comprising the steps of:

4 simultaneously receiving to at least one of the input ports at least two optical
5 signals respectively colored as a function of destination information contained
6 therein; and

7 simultaneously presenting from at least one of the output ports at least two
8 optical signals routed as a function of their color.

1 **23.** The method of Claim **22**, further comprising the step of processing each of
2 the presented at least two routed optical signals from the at least one of the
3 output ports.

1 **24.** The method of Claim **22**, wherein the step of simultaneously applying to at
2 least one of the input ports comprises the step of coloring each optical signal of
3 the plurality is a further function of which input port of the plurality it is applied
4 to.

1 **25.** A method for use in conjunction with a router which has a plurality of
2 input ports and a plurality of output ports, said router being of a type which
3 routes optical signals applied to its input ports to particular ones of said output
4 ports as a function of the respective colors of said optical signals, the method:

5 applying each of a plurality of optical signals to a respective one of the
6 input ports, this step including the step of concurrently applying to an
7 individual one of said input ports at least two optical signals which have
8 been respectively colored as a function of destination information
9 contained in said optical signals, at least two of said optical signals being
10 concurrently routed to a particular one of said output ports.

1 **26.** The invention of claim **25**, comprising the further step of concurrently
2 removing from said particular one of said output ports said two optical signals
3 concurrently routed thereto.

1 **27.** The invention of claim **25**, wherein the coloring of each said optical signal
2 is a further function of which input port it is applied to.

ABSTRACT

An optical router is disclosed having at least one frequency router. The frequency router includes a plurality of input ports and a plurality of output ports. At least one input port simultaneously receives at least two optical signals to be frequency routed, while at least one output port simultaneously presents at least two frequency routed optical signals. Each optical signal to be frequency routed is colored in response to destination information.

0054832 032500

10




FIG. 1

50




FIG. 2




FIG. 3

005239-20040900




FIG 4




FIG. 5

005280" 4584960




FIG. 6




FIG. 7

600 ↘




FIG. 8

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

Declaration and Power of Attorney

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled **Optical Router** the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by an amendment, if any, specifically referred to in this oath or declaration.

I acknowledge the duty to disclose all information known to me which is material to patentability as defined in Title 37, Code of Federal Regulations, 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

None

I hereby claim the benefit under Title 35, United States Code, 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

None

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorney(s) with full power of substitution and revocation, to prosecute said application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

0964832-08500

Thomas J. Bean	(Reg. No. 44528)
Lester H. Birnbaum	(Reg. No. 25830)
Richard J. Botos	(Reg. No. 32016)
Jeffery J. Brosemer	(Reg. No. 36096)
Kenneth M. Brown	(Reg. No. 37590)
Donald P. Dinella	(Reg. No. 39961)
Martin I. Finston	(Reg. No. 31613)
William S. Francos	(Reg. No. 38456)
Barry H. Freedman	(Reg. No. 26166)
Julio A. Garceran	(Reg. No. 37138)
Jimmy Goo	(Reg. No. 36528)
Anthony Grillo	(Reg. No. 36535)
Stephen M. Gurey	(Reg. No. 27336)
John M. Harman	(Reg. No. 38173)
Matthew J. Hodulik	(Reg. No. 36164)
Michael B. Johannesen	(Reg. No. 35557)
Mark A. Kurisko	(Reg. No. 38944)
Irena Lager	(Reg. No. 39260)
John B. MacIntyre	(Reg. No. 41170)
Christopher N. Malvone	(Reg. No. 34866)
John F. McCabe	(Reg. No. 42854)
Scott W. McLellan	(Reg. No. 30776)
Martin G. Meder	(Reg. No. 34674)
John C. Moran	(Reg. No. 30782)
Michael A. Morra	(Reg. No. 28975)
Gregory J. Murgia	(Reg. No. 41209)
Claude R. Narcisse	(Reg. No. 38979)
Joseph J. Opalach	(Reg. No. 36229)
Neil R. Ormos	(Reg. No. 35309)
Eugen E. Pacher	(Reg. No. 29964)
Jack R. Penrod	(Reg. No. 31864)
Gregory C. Ranieri	(Reg. No. 29695)
Scott J. Rittman	(Reg. No. 39010)
Ferdinand M. Romano	(Reg. No. 32752)
Eugene J. Rosenthal	(Reg. No. 36658)
Bruce S. Schneider	(Reg. No. 27949)
Ronald D. Slusky	(Reg. No. 26585)
David L. Smith	(Reg. No. 30592)
Ozer M. N. Teitelbaum	(Reg. No. 36698)
John P. Veschi	(Reg. No. 39058)
David Volejnicek	(Reg. No. 29355)
Charles L. Warren	(Reg. No. 27407)
Jeffrey M. Weinick	(Reg. No. 36304)
Eli Weiss	(Reg. No. 17765)

Please address all correspondence to the Docket Administrator (Rm. 3C-512), Lucent Technologies Inc., 600 Mountain Avenue, P. O. Box 636, Murray Hill, New Jersey 07974-0636. Telephone calls should be made to Ozer M.N. Teitelbaum by dialing 908-582-3246.

005230 2284960

Full name of 1st joint inventor: Jurgen Gripp

Inventor's signature Jürgen Gripp Date 8/23/2000

Residence: Cranford, Monmouth County, New Jersey

Citizenship: Fed. Rep. of Germany

Post Office Address: 217 Prospect Avenue
Apt 6-1A
Cranford, New Jersey, 07016

Full name of 2nd inventor: Martin Zirngibl

Inventor's signature Martin Zirngibl Date 8/23/2000

Residence: Middletown, Monmouth County, New Jersey

Citizenship: Fed. Rep. of Germany

Post Office Address: 30 Hunterspoint Road
Middletown, New Jersey, 07748

005280" 23824960